



ORLEN OIL MULTI STOU 10W-40

General features

Multi STOU 10W-40 is a high-quality synthetic oil of the Super Tractor Oil Universal type. It is characterised by a very high level of protection for engines working in difficult conditions. Thanks to its carefully chosen formulation it provides excellent lubrication for all kinds of manual transmissions.

Application

Multi STOU 10W-40 is a universal oil which can be used in machine engines, manual gearboxes. It can be successfully used in hydraulic systems and wet brakes.

Quality class

API: CG-4 API: GL-4

ACEA: E3

Viscosity grad

SAE: 10W-40

Standards, approvals, specifications

Meets requirements:

Massey Ferguson M1145,
Massey Ferguson M1144,
Massey Ferguson M1139
Ford M2C 159B,
Ford M2C 159C,
John Deere JDM J27,
New Holland 82009201,
New Holland 82009202,
New Holland 82009203
ZF TE –ML 06A ,
ZF TE –ML 06B,
ZF TE –ML 06C,
ZF TE –ML 07B
CCMS D4,
Sperry Vickers/Eaton: M2950S,
Sperry Vickers/Eaton: I-286-S,
Sauer Sunstrand/Danfoss: Hydrostatic Trans Fluid,
AFNOR NFE68603E .

Physical and chemical properties

Parameters	Unit	Typical values
SAE viscosity grade	-	10W-40
kinematic viscosity at 100°C	mm ² /s	14,4
viscosity index	-	153
flow temperature	°C	-45
flash-point	°C	216
TBN number	Mg KOH/g	10,9

Note: Physicochemical parameters listed in the table are typical values. Real values are stated in quality control certificates attached to each production batch.

Version 2 / 2024-02-27